

4XEM's USB-C Dual 4K with Power Delivery Universal Docking Station

4XEM Part- 4XUG69PD2



4XEM's USB-C Power Delivery Docking Station is a dual use device to charging and display. This docking station supports USB Power Delivery (up to 60-80 Watts Max. for Laptop charging), so you can power and charge your laptop directly through its USB-C port. Because a single power adapter can be used for your dock and laptop, you can reduce clutter at your workstation. You can easily connect your DisplayPort and HDMI monitors due to the new USB Type-C connector which works seamlessly with this Dual 4K Universal Docking Station. Plus, you don't need to carry or remember an extra power adapter when you're traveling to or from the office thanks to its charging capabilities. Multi-task with 4XEM's USB-C Dual 4K Power Delivery Docking Station

**Including the latest drivers for compatibility with Windows 10, 8, and 7 or Apple Mac OS**

**4XEM Products Are Available At Your Favorite Online Retailers**

**WWW.4XEM.COM**

**Contact Todd Schaus 4XEM sales Rep  
1-866-999-4936 Ext.104    tschaus@4xem.com**



## Features

- USB3.1 Type-C and Standard-A connectors compatible both Type-C Laptop
- 100Watt Power Adapter support 60Watt upstream Laptop Charging, and 40Watt power for all downstream devices
- Build in USB 3.0 GPU, Plug and Display Certified by DisplayLink
- 2 x DP++ (Dual Mode DP1.2) support resolution up to (4K)4096 x 2160p6
- Support resolution 5k)5120 x 2880p60 when only using one DP++ port
- Support Extend and Mirror Video Mode. 5.1 Channel surround-sound through Display Port interface
- Gigabit Ethernet network RJ-45 backward 10/100 Ethernet
- 2.0 Audio Line-out Jack for Earphone and Line-In Jack Microphone
- 4 x USB 3.0 downstream ports, and 2 x USB-C Gen1, one Type-A port placed at the front support BC1.2 fast charging to devices

## Application

- Home theatre
- Small business
- Home Office
- Business Presentations

**4XEM Products Are Available At Your Favorite Online Retailers**





**DATA SHEET**

Warranty Information	Warranty	2 Years
Hardware	4K Support Displays Supported USB Ports Fast-Charge Port(s) Network SD Card Reader Audio Host Bus Type Power Delivery Lock Slot Industry Standards  Chipset ID	Yes 2 6 Yes Yes No Yes USB 3.1 Gen 1 Type-C Yes Yes DP 1.2 HDMI 2.0 HDCP 1.4 Power Delivery 2.0 Battery Charge 1.2 DisplayLink DL6950 FrescoLogic FL5002 VIA VL813 RealTek RTL8211F
Connector(s)	Host Connector Host Connector Cable Connector Type(s)/Rate(s)	USB 3.1 Gen 1 Type-C (5Gbps) Detachable 2x DisplayPort++ 1.2 (HBR2: 5.40Gbps x4) 2x HDMI 2.0 (18Gbps) 2x USB 3.1 Gen 1 Type-C (5Gbps) 1x USB 3.0 Type-A (5Gbps - Quick Charge 2.4A) 3x USB 3.0 Type-A (5Gbps) 1x RJ-45 (10/100/1000Mbps) 1x 3-Pole TRS Phono Jack (Audio In - Microphone) 1x 3-Pole TRS Phono Jack (Audio Out - Speakers/Headphones)
Performance	Maximum Digital Resolutions	Single Monitor: 5K (5120 x 2880 @ 60Hz) Dual Monitors: 4K UHD (3840 x 2160 @ 60Hz) Each
Software	OS Compatibility	Windows 7, 8, 10 Mac OS
Power	Power Source Power Adaptor Style Power Consumption Input Voltage Input Current Output Voltage Output Current Power Delivery	AC Adaptor Included (100-240VAC, 50/60Hz, 2.5A Max., CLASS II) Brick 100W 20V DC 5A 20V DC 3A + 2A 60W to Host 40W for Peripherals
Physical Characteristics	Product Height Product Width Product Length Weight of Product Color Material Cable Length Power Button Power LED	1.20 in [30.5 mm] 8.78 in [223 mm] 3.31 in [84 mm] 12.20 oz [346 g] Black ABS Plastic 36 in [0.91 m] Switch Blue
Environmental	Operating Temperature Storage Temperature Humidity	0°C~40°C -10~70°C 10%~90%noncondensing
Packaging Information	Shipping (Package) Weight Package Height Package Width Package Length	2.91 lbs [1.32 kg] 4.02 in [102 mm] 10.51 in [267 mm] 5.39 in [137 mm]
What's in the Box	Included in Package	1x USB-C Universal Docking Station 1x USB-C to USB-C Cable 1x USB-C to USB-A Cable 1x User Manual 1x DC20V/5A Power Adapter (46" fixed output cable) 1x NEMA 5-15P to IEC 320 C5 (55" long)
Country of Origin	Country of Origin	China
Notes	*HDCP not supported on Mac OS. Power Delivery not supported when using included USB-C to USB-A cable. If both video output ports are occupied on the same display head, DisplayPort will be given priority. Audio output is not dynamically selectable and is given the following priority: 1) 3.5mm Phono Jack - 2) Display Head 1 - 3) Display Head 2"	

\* Product appearance and specifications are subject to change without notice.

\* Same day shipping is only available for orders shipping within the United States.

**4XEM Products Are Available At Your Favorite Online Retailers**

**WWW.4XEM.COM**

**Contact Todd Schaus 4XEM sales Rep  
1-866-999-4936 Ext.104    tschaus@4xem.com**

