

4XEM's USB-C Travel Mini Dock

4XEM Part- 4XUHP3407



4XEM's USB-C Mini Dock brings a unique travelling design for USB devices to deliver multi ports in the smallest footprint. Sporting a HDMI USB3.1 VESA Alt. Mode port this dock is still able to support 4K resolution to present dual UHD 4K display. Additionally, it has 2 USB 3.0-A Hub ports and one USB-C can upstream power charging or data transferring. This compact Mini Dock to replace all other dongles be one for portable user. With an innovative design, the product has been widely acclaimed by Apple fans. 4XEM's believes you too will approve of this sleek, unique, and amazingly portable dock.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep
1-866-999-4936 Ext.104 tschaus@4xem.com



Features

- Unique and slim aluminum design Mini Dock for handy travelling purpose.
- Build in one HDMI V1.4 via USB3.1 (VESA Alternate Mode) video output support max. resolution up to 4K@30Hz.
- Two USB-A ports extended USB3.0 (5Gbps) data transferring, backward USB2.0 compliance.
- One USB-C port support USB Power Delivery maximum 60 watts upstream power charging to PC or as be a device USB3.0 data transferring.
- Minimum from 5-10 watts of power supplied to downstream devices depends on a different power rating of Type-C PD power adapter.
- Build in Billboard function.
- Combo built in individual R/W USB3.0 SD and Micro SD Card Reader. Support SD V1.0/ v1.1/ v2.0/ V3.01 and V5.0, SDHC/ SDXC (Capacity up to 2TB).

Application

- Home theatre
- Small business
- Travelling
- Business Presentations

4XEM Products Are Available At Your Favorite Online Retailers





DATA SHEET

Warranty Information	Warranty	2 Years
Hardware	4K Support Displays Supported USB Ports Fast-Charge Port(s) Network SD Card Reader Audio Host Bus Type Power Delivery Lock Slot Industry Standards Chipset ID	Yes 1 2 N/A No Yes No USB Type-C PD Pass-through No HDMI 1.4 HDCP 1.4 HDCP 2.3 SD v3.01 Power Delivery (PD 2.0) Fresco Logic FL5002 Parade Technologies PS176 Genesys Logic GL3224
Connector(s)	Host Connectors Host Connector Cable Connector Type(s)/Rate(s)	USB 3.1 Gen 1 Type-C (5Gbps) Fixed Attached 1x HDMI 1.4 (10.2 Gbps) 1x USB 3.1 Gen 1 Type-C (5Gbps - Or USB-C Power Adaptor for PD) 2x USB 3.0 Type-A (5Gbps) 1x SD Card Reader (SD v3.01) 1x Micro SD Card Reader (SD v3.01)
Performance	Maximum Digital Resolutions	4K UHD (3840 x 2160 @ 30Hz)
Software	OS Compatibility	Windows 10 Mac OSX
Power	Power Source Power Adaptor Style Power Consumption Input Voltage Input Current Output Voltage Output Current Power Delivery	Bus Powered or USB-C Power Adaptor (Not Supplied) for PD N/A 15W (full load without PD) 5V DC 3A PD Pass-through (dependant on Power adaptor input) PD Pass-through (dependant on Power adaptor input) PD Pass-through (dependant on Power adaptor input)
Physical Characteristics	Product Height Product Width Product Length Weight of Product Color Material Cable Length Power Button Power LED	0.45 in [11.4 mm] 5.25 in [133.3 mm] 1.42 in [36.1 mm] 2.75 oz [78 g] Grey Aluminum 20 in [508 mm] N/A Blue
Environmental	Operating Temperature Storage Temperature Humidity	0°C~40°C -10~70°C 10%~90%,noncondensing
Packaging Information	Shipping (Package) Weight Package Height Package Width Package Length	5.01 oz [142 g] 3.62 in [92 mm] 3.11 in [79 mm] 1.00 in [25.3 mm]
What's in the Box	Included in Package	1x USB-C Mini Travel Dock 1x User Manual
Country of Origin	Country of Origin	China
Notes		"DP Alt mode support required from host for HDMI output. 2 SuperSpeed data lanes used for DP Alt mode, 2 remaining SuperSpeed data lanes used for remaining functions."

* Product appearance and specifications are subject to change without notice.

* Same day shipping is only available for orders shipping within the United States.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

**Contact Todd Schaus 4XEM sales Rep
1-866-999-4936 Ext.104 tschaus@4xem.com**

