

**DATA SHEET** 

4XEM's USB-C Triple Display Docking Station with Power Delivery (2 DP + 1HDMI)

4XEM Part- 4XUMD02



4XEM's USB-C Triple Display Docking Station delivers device charging to your Laptop Computer, supports up to three displays, and enables connectivity to your wired network and other accessories. Sporting 2 DisplayPort USB ports and one HDMI port connect compatible devices easily. Organize your cables and de-clutter any device heavy space while staying charged and connected with this versatile Docking Station.

**4XEM Products Are Available At Your Favorite Online Retailers** 

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com





## **Features**

- Compatible with Type-C USB3.1 Gen2 full specification PC Computer
- USB Power Delivery with 4 profile support 65 Watts upstream charging
- DisplayPort support V1.4; HDMI port support HDMI V2.0
- Support triple display, max. resolution up to 1920x1080@60 (HBR3 DP1.3)
- Support dual display, max. resolution up to 2560x1440@60 (HBR3 DP1.3)
- Support single display, max. resolution up to 3840x2160@60 (HBR3 DP1.3)
- Build in Gigabit Ethernet network RJ-45 backward 10/100 Ethernet
- Build in 4-Pole phone Jack for stereo audio out and microphone in
- Build in Combo SD / TF Card Reader SD V3.01 support SDHC / SDXC capacity up to 2TB
- Four USB 3.0 Type-A ports with one port has BC1.2 fast charging
- Support OS Windows 7 / 8 / 10; Max OSX 10 or the latest version

## **Application**

- Home theatre
- Small business
- Multi-Screen Display
- Business Presentations

4XEM Products Are Available At Your Favorite Online Retailers

Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com



## **DATA SHEET**

Warranty Information

4K Support

Displays Supported USB Ports Fast-Charge Port(s) Yes Yes Yes USB Type-C SD Card Reader Host Bus Type

Power Delivery 65W Yes Lock Slot Industry Standards Power Delivery (PD 3.0)

Display Port 1.4 (HBR3) HDMI 2.0 HDCP 2.3 Battery Charging (BC 1.2) Chipset ID

Fresco Logic - FL5002 Fresco Logic - FL5000 Synaptics - VMM5320 Realtek - RTL8153B Realtek - Al C4030 Genesys Logic - GL3224

Connector(s) Host Connectors USB 3.1 Gen 2 Type-C (10 Gbps) Detatchable

2x DisplayPort++ 1.4 (HBR3 8.1 Gbps x4)

1x HDMI 2.0 (18 Gbps) Host Connector Cable Connector Type(s)/Rate(s)

1x USB 3.0 Type-A (5 Gbps)
1x USB 3.0 Type-A (5 Gbps - BC 1.2 Fast Charge)
1x RJ-45 (10/100/1000 Mbps)

Yes

1x SD Card Reader (SD 3.01) 1x MicroSD Card Reader (SD 3.01)

1x 4-Pole TRRS 3.5mm Audio Jack (Stereo/Mic Combo) Performance Maximum Digital Resolutions

HBR3 Single Monitor: 4K UHD (3840 x 2160 @ 60Hz) HBR3 Single Monitor: 4K UHD (3840 x 2160 @ 60Hz) Each HBR3 Dual Monitor: WOHD (2660 x 1440 @ 60Hz) Each HBR3 Triple Monitor: FHD (1920 x 1080 @ 60Hz) Each HBR2 Single Monitor: 4K UHD (3840 x 2160 @ 30Hz) HBR2 Dual Monitor: FHD (1920 x 1080 @ 60Hz) Each HBR2 Dual Monitor: HD+ (1600 x 900 @ 60Hz) Each

OS Compatibility Windows 7, 8, 10

AC Adapter Included (100-240VAC, 50/60Hz, 1.5A Max, CLASS II ) Power Source Power Adaptor Style

Power Consumption 100W 20V DC Input Current 5A 20V DC Output Voltage Output Current Power Delivery 3.25A 65W

0.79 in [20 mm] 8.15 in [207 mm] 3.27 in [83 mm] Product Height Physical Characteristics Product Length

Weight of Product Color 11.36 oz [322 g] Black Plastic 37 in [940 mm] Cable Length Power Button Tact Switch Button Power LED

Operating Temperature Storage Temperature Humidity 0°C~40°C

Shipping (Package) Weight Package Height Package Width 2.65 lbs [1.20 kg] 5.12 in [130 mm] Package Length

1x Triple Monitor MST Dock 1x USB Type-C Cable (E-Marked) 1x Quick Start Guide Included in Package What's in the Box

1 x DC2OV/5A 100W Power Adapter (46" fixed output cable) 1x NEMA 5-15P to IEC 320 C13 Power Cable (55" long)

Country of Origin Country of Origin

Uses 2 DisplayPort lanes of USB-C connection for video output

total video bandwidth cannot exceed host connection bandwidth.

Some graphics chipsets support only a limited number of active displays resulting in one or more of the displays connected to the 4XUMD02 left blank - Active displays can be changed in the display \* Product appearance and specifications are subject to change without notice.

settings of your operating system."

\* Same day shipping is only available for orders shipping within the United States.

## 4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Packaging Information

Notes

**Contact Todd Schaus 4XEM sales Rep** 1-866-999-4936 Ext.104 tschaus@4xem.com

"DP-Alt Mode required from host for video output.

