

4XEM's USB-C Triple Display Docking Station with Power Delivery (2HDMI + 1DP)

4XEM Part- 4XUMD06



4XEM's USB-C Triple Display Docking Station delivers device charging to your Laptop Computer, supports up to three displays, and enables connectivity to your wired network and other accessories. Sporting 2 HDMI ports and one DisplayPort connect compatible devices easily. Organize your cables and de-clutter any device heavy space while staying charged and connected with this versatile Docking Station.

**4XEM Products Are Available At Your Favorite Online Retailers**

**WWW.4XEM.COM**

Contact Todd Schaus 4XEM sales Rep  
1-866-999-4936 Ext.104    [tschaus@4xem.com](mailto:tschaus@4xem.com)



## Features

- Compatible with Type-C USB3.1 Gen2 full specification PC Computer
- USB Power Delivery with 4 profile support 65 Watts upstream charging
- DisplayPort support V1.4; HDMI port support HDMI V2.0
- Support triple display, max. resolution up to 1920x1080@60 (HBR3 DP1.3)
- Support dual display, max. resolution up to 2560x1440@60 (HBR3 DP1.3)
- Support single display, max. resolution up to 3840x2160@60 (HBR3 DP1.3)
- Build in Gigabit Ethernet network RJ-45 backward 10/100 Ethernet
- Build in 4-Pole phone Jack for stereo audio out and microphone in
- Build in Combo SD / TF Card Reader SD V3.01 support SDHC / SDXC capacity up to 2TB
- Four USB 3.0 Type-A ports with one port has BC1.2 fast charging
- Support OS Windows 7 / 8 / 10; Max OSX 10 or the latest version

## Application

- Home theatre
- Small business
- Multi-Screen Display
- Business Presentations

**4XEM Products Are Available At Your Favorite Online Retailers**





## DATA SHEET

Warranty Information	Warranty	2 Years
Hardware	4K Support Displays Supported USB Ports Fast-Charge Port(s) Network SD Card Reader Audio Host Bus Type Power Delivery Lock Slot Industry Standards  Chipset ID	Yes 3 4 1 Yes Yes Yes USB Type-C 65W Yes Power Delivery (PD 3.0) Display Port 1.4 (HBR3) HDMI 2.0 HDCP 2.3 Battery Charging (BC 1.2) Fresco Logic - FL5002 Fresco Logic - FL5000 Synaptics - VMM5310 Realtek - RTL8153B Realtek - ALC4030 Genesys Logic - GL3224
Connector(s)	Host Connectors Host Connector Cable Connector Type(s)/Rate(s)	USB 3.1 Gen 2 Type-C (10 Gbps) Detachable 1x DisplayPort++ 1.4 (HBR3 8.1 Gbps x4) 2x HDMI 2.0 (18 Gbps) 3x USB 3.0 Type-A (5 Gbps) 1x USB 3.0 Type-A (5 Gbps - BC 1.2 Fast Charge) 1x RJ-45 (10/100/1000 Mbps) 1x SD Card Reader (SD 3.01) 1x MicroSD Card Reader (SD 3.01) 1x 4-Pole TRRS 3.5mm Audio Jack (Stereo/Mic Combo)
Performance	Maximum Digital Resolutions	HBR3 Single Monitor: 4K UHD (3840 x 2160 @ 60Hz) HBR3 Dual Monitor: WQHD (2560 x 1440 @ 60Hz) Each HBR3 Triple Monitor: FHD (1920 x 1080 @ 60Hz) Each HBR2 Single Monitor: 4K UHD (3840 x 2160 @ 30Hz) HBR2 Dual Monitor: FHD (1920 x 1080 @ 60Hz) Each HBR2 Triple Monitor: HD+ (1600 x 900 @ 60Hz) Each
Software	OS Compatibility	Windows 7, 8, 10 Mac OS X
Power	Power Source Power Adaptor Style Power Consumption Input Voltage Input Current Output Voltage Output Current Power Delivery	AC Adapter Included (100-240VAC, 50/60Hz, 1.5A Max, CLASS II) Brick 100W 20V DC 5A 20V DC 3.25A 65W
Physical Characteristics	Product Height Product Width Product Length Weight of Product Color Material Cable Length Power Button Power LED	0.79 in [20 mm] 8.15 in [207 mm] 3.27 in [83 mm] 11.36 oz [322 g] Black Plastic 37 in [940 mm] Tact Switch Button Blue
Environmental	Operating Temperature Storage Temperature Humidity	0°C~40°C 10%~90%,noncondensing 10%~90%,noncondensing
Packaging Information	Shipping (Package) Weight Package Height Package Width Package Length	2.65 lbs [1.20 kg] 2.95 in [75 mm] 10.51 in [267 mm] 5.12 in [130 mm]
What's in the Box	Included in Package	1x Triple Monitor MST Dock 1x USB Type-C Cable (E-Marked) 1x Quick Start Guide 1 x DC20V/5A 100W Power Adapter (46" fixed output cable) 1x NEMA 5-15P to IEC 320 C13 Power Cable (55" long)
Country of Origin	Country of Origin	China
Notes	Notes	*DP-Alt Mode required from host for video output. Uses 2 DisplayPort lanes of USB-C connection for video output. Total video bandwidth cannot exceed host connection bandwidth. Some graphics chipsets support only a limited number of active displays resulting in one or more of the displays connected to the 4XUMD06 left blank - Active displays can be changed in the display settings of your operating system."

\* Product appearance and specifications are subject to change without notice.

\* Same day shipping is only available for orders shipping within the United States.

### 4XEM Products Are Available At Your Favorite Online Retailers

[WWW.4XEM.COM](http://WWW.4XEM.COM)

Contact Todd Schaus 4XEM sales Rep  
1-866-999-4936 Ext.104    [tschaus@4xem.com](mailto:tschaus@4xem.com)

