

4XEM's Thunderbolt 3 4K Display Universal Docking Station Model 2

4XEM Part- 4XUTD01H



Sleek and compact 4XEM's powerful Thunderbolt 3 Universal Docking Station, is offering single-cable connectivity to large high-resolution monitors or multiple monitors. The station also allows the user to gain access to faster Ethernet connectivity. As well as connectivity to any headset, microphone, or memory card reader regardless of the laptop they have.

Compatible with Mac or Windows, connect single display up to 4K 60Hz via the integrated DisplayPort output or an HDMI display by using provided active DisplayPort to HDMI Adapter. Access dual display by adding one more USB-C to DP/HDMI adapter connected to Thunderbolt 3 port.

The dock is two times faster than Thunderbolt 2 and eight times faster than USB 3.0, transferring of a full 4K movie in under 30 seconds, delivering speeds up to 40Gbps. With this unprecedented speed, you can continuously transfer large files to external backup storage or retrieve data from other storage devices quickly without compromising bandwidth from your 4K displays.

Connect displays, improve resolution, and transfer with new speed all with 4XEM's Thunderbolt 3 Universal Docking Station.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep
1-866-999-4936 Ext.104 tschaus@4xem.com



Features

- Thunderbolt 3 4K Universal Docking Station provides USB power delivery up to 100W maximum of upstream charging to compatible Thunderbolt 3 host systems and also, power to the other peripherals simultaneously with 180Watt Power Adapter.
- Integrated DisplayPort support 4K 60Hz (4096×2160@60Hz) or an HDMI display using the included accessories Active DisplayPort to HDMI 2.0 adapter.
- The second Thunderbolt 3 port placed at the front supports up to 5 daisy chained Thunderbolt 3 devices or a single USB 3.1 Gen 2 (up to 10Gbps) device.
- One USB3.0 port placed at the front and three USB3.0 port placed at the back to give more USB devices connectivity.
- Integrated RJ45 Gigabit Ethernet provide secure, reliable high speed wired networks
- Integrated SD/Micro SD Card Reader easy for copy any photos or movies from your media memory card backup to your PC directly.
- Integrated a combo audio headset, microphone port
- Mechanic security lock

Application

- Home theatre
- Small business
- Multi-Screen Display
- Business Presentations

4XEM Products Are Available At Your Favorite Online Retailers



Warranty Information	Warranty	2 Years	
Hardware	4K Support	Yes	
	Displays Supported	2	
Connector(s)	USB Ports	4	
	Fast-Charge Port(s)	No	
	Network	Yes	
	SD Card Reader	Yes	
	Audio	Yes	
	Host Bus Type	Thunderbolt 3	
	Power Delivery	85W + 60W	
	Lock Slot	Yes	
	Industry Standards	DisplayPort 1.2 (HBR2)	
	Chipset ID		HDMI 2.0 (Only available on 4XUTD03H)
			HDCP (Version depends on host GPU)
			Battery Charging (BC 1.2)
			Alpine Ridge JHL6540
			Texas Instruments TPS65983
			Fresco Logic FL1100
		Fresco Logic FL5000	
		Realtek RTL8153	
		Genesys Logic GL3224	
		Realtek ALC4040	
Performance	Host Connector	1x Thunderbolt 3 (40Gbps)	
	Host Connector Cable	Detachable	
	Connector Type(s)/Rate(s)		1x DisplayPort 1.2 (HBR2: 5.40Gbps x4)
			1x Thunderbolt 3 (40Gbps - DP Alt Mode - USB Mode: Max 10Gbps)
			1x USB 3.0 Type-A (5Gbps - Quick Charge: 2.4A)
			3x USB 3.0 Type-A (5Gbps)
			1x RJ45 (10/100/1000/Mbps)
			1x SD Card Reader (SD 3.0)
			1x MicroSD Card Reader (MicroSD 3.0)
			1x 4-pole TRRS Phono Jack (Stereo/Mic Combo)
Maximum Digital Resolutions	Single Monitor: 5K (5120 x 2880 @ 60Hz)		
	Dual Monitors: 4K UHD (3840 x 2160 @ 60Hz) Each		
Software	OS Compatibility	Windows 10 Mac OSX	
Power	Power Source	AC Adapter Included (100-240VAC, 50/60Hz, 2A Max , CLASS II)	
	Power Adaptor Style	Brick	
	Power Consumption	145W	
	Input Voltage	20V DC	
	Input Current	9A	
	Output Voltage	20V DC	
	Output Current	4.25A + 3A	
Power Delivery	85W to Host 60W to Peripherals		
Physical Characteristics	Product Height	1.28 in [31.9 mm]	
	Product Width	8.50 in [216 mm]	
	Product Length	3.65 in [92.8mm]	
	Weight of Product	12.63 oz [358 g]	
	Color	Grey and Black	
	Material	Aluminium and Plastic	
	Cable Length	24 in [610 mm]	
	Power Button	Tact Switch Button	
	Power LED	Blue	
Environmental	Operating Temperature	0°C to 40°C	
	Storage Temperature	-10°C to 70°C	
	Humidity	10% to 90% (non-condensing)	
Packaging Information	Shipping (Package) Weight	2.96 lbs [1.34 kg]	
	Package Height	3.12 in [81 mm]	
	Package Width	10.24 in [260 mm]	
	Package Length	7.56 in [192 mm]	
What's in the Box	Included in Package	1 x Thunderbolt™ 3 Universal Docking Station 1 x Thunderbolt™ 3 40Gbps cable 0.7 meter 1 x User Manual 1 x Active DP to HDMI Adapter (Only included in UTD03H) 1 x DC20V/9A 180W Power Adapter (46" fixed outout cable) 1 x NEMA 5-15P to IEC 320 C13 Power Cable (55" long)	
Country of Origin	Country of Origin	China	

* Product appearance and specifications are subject to change without notice.

* Same day shipping is only available for orders shipping within the United States.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep
1-866-999-4936 Ext.104 tschaus@4xem.com

